



ADDICT GRAVEL, SPEEDSTER GRAVEL

SPEEDSTER GRAVEL: 10, 20, 30, 40, 50

	XXS/47		XS/49		S/52		M/54		L/56		XL/58		XXL/61	
A HEAD TUBE ANGLE	70.0°		70.0°		70.0°		71.0°		71.0°		71.0°		71.0°	
B HEAD TUBE LENGTH	93.0 mm	3.7 in	103.0 mm	4.1 in	123.0 mm	4.8 in	143.0 mm	5.6 in	163.0 mm	6.4 in	183.0 mm	7.2 in	203.0 mm	8.0 in
C TOP TUBE HORIZONTAL	512.3 mm	20.2 in	523.0 mm	20.6 in	536.5 mm	21.1 in	556.5 mm	21.9 in	571.2 mm	22.5 in	581.2 mm	22.9 in	594.2 mm	23.4 in
D STANDOVER HEIGHT	747.0 mm	29.4 in	762.0 mm	30.0 in	786.0 mm	30.9 in	806.0 mm	31.7 in	825.0 mm	32.5 in	844.0 mm	33.2 in	869.0 mm	34.2 in
E BB OFFSET	-71.0 mm	-2.8 in	-71.0 mm	-2.8 in	-71.0 mm	-2.8 in	-71.0 mm	-2.8 in	-71.0 mm	-2.8 in	-71.0 mm	-2.8 in	-71.0 mm	-2.8 in
F BB HEIGHT	283.0 mm	11.1 in	283.0 mm	11.1 in	283.0 mm	11.1 in	283.0 mm	11.1 in	283.0 mm	11.1 in	283.0 mm	11.1 in	283.0 mm	11.1 in
G WHEEL BASE	1019.5 mm	40.1 in	1026.9 mm	40.4 in	1037.7 mm	40.9 in	1044.9 mm	41.1 in	1056.4 mm	41.6 in	1067.0 mm	42.0 in	1071.3 mm	42.2 in
H BB CENTER TO TOPTUBE CENTER	430.0 mm	16.9 in	450.0 mm	17.7 in	480.0 mm	18.9 in	500.0 mm	19.7 in	520.0 mm	20.5 in	540.0 mm	21.3 in	570.0 mm	22.4 in
I BB CENTER TO TOP OF SEATTUBE	470.0 mm	18.5 in	490.0 mm	19.3 in	520.0 mm	20.5 in	540.0 mm	21.3 in	560.0 mm	22.0 in	580.0 mm	22.8 in	610.0 mm	24.0 in
J SEAT ANGLE	75.0°		74.5°		74.0°		73.0°		72.5°		72.5°		72.5°	
K CHAINSTAY	435.0 mm	17.1 in	435.0 mm	17.1 in	435.0 mm	17.1 in	439.0 mm	17.3 in	439.0 mm	17.3 in	439.0 mm	17.3 in	439.0 mm	17.3 in
L REACH	374.0 mm	14.7 in	378.0 mm	14.9 in	382.0 mm	15.0 in	387.0 mm	15.2 in	392.0 mm	15.4 in	396.0 mm	15.6 in	403.0 mm	15.9 in
M STACK	519.0 mm	20.4 in	528.4 mm	20.8 in	547.2 mm	21.5 in	570.0 mm	22.4 in	588.9 mm	23.2 in	607.8 mm	23.9 in	626.8 mm	24.7 in
N STEM LENGTH	73.0 mm	2.9 in	83.0 mm	3.3 in	93.0 mm	3.7 in	103.0 mm	4.1 in	103.0 mm	4.1 in	113.0 mm	4.4 in	113.0 mm	4.4 in