



ADDICT RC, ADDICT, SPEEDSTER

	XXS/47		XS/49		S/52		M/54		L/56		XL/58		XXL/61	
A HEAD TUBE ANGLE	70.5°		71.0°		72.0°		72.5°		73.0°		73.3°		73.3°	
B HEAD TUBE LENGTH	110.0 mm	4.3 in	115.0 mm	4.5 in	130.0 mm	5.1 in	150.0 mm	5.9 in	170.0 mm	6.7 in	190.0 mm	7.5 in	210.0 mm	8.3 in
C TOP TUBE HORIZONTAL	510.0 mm	20.1 in	520.0 mm	20.5 in	535.0 mm	21.1 in	550.0 mm	21.7 in	565.0 mm	22.2 in	580.0 mm	22.8 in	595.0 mm	23.4 in
D STANDOVER HEIGHT	715.9 mm	28.2 in	729.4 mm	28.7 in	753.6 mm	29.7 in	773.5 mm	30.5 in	798.8 mm	31.4 in	812.9 mm	32.0 in	837.3 mm	33.0 in
E BB OFFSET	-66.0 mm	-2.6 in	-66.0 mm	-2.6 in	-66.0 mm	-2.6 in	-66.0 mm	-2.6 in	-66.0 mm	-2.6 in	-66.0 mm	-2.6 in	-66.0 mm	-2.6 in
F BB HEIGHT	273.0 mm	10.7 in	273.0 mm	10.7 in	273.0 mm	10.7 in	273.0 mm	10.7 in	273.0 mm	10.7 in	273.0 mm	10.7 in	273.0 mm	10.7 in
G WHEEL BASE	972.0 mm	38.3 in	978.0 mm	38.5 in	980.0 mm	38.6 in	987.0 mm	38.9 in	994.2 mm	39.1 in	1,002.9 mm	39.5 in	1,012.0 mm	39.8 in
H BB CENTER TO TOPTUBE CENTER	400.0 mm	15.7 in	420.0 mm	16.5 in	450.0 mm	17.7 in	470.0 mm	18.5 in	490.0 mm	19.3 in	510.0 mm	20.1 in	540.0 mm	21.3 in
I BB CENTER TO TOP OF SEATTUBE	410.0 mm	16.1 in	430.0 mm	16.9 in	460.0 mm	18.1 in	480.0 mm	18.9 in	500.0 mm	19.7 in	520.0 mm	20.5 in	550.0 mm	21.7 in
J SEAT ANGLE	74.5°		74.5°		74.0°		73.6°		73.3°		73.0°		72.5°	
K CHAINSTAY	410.0 mm	16.1 in	410.0 mm	16.1 in	410.0 mm	16.1 in	410.0 mm	16.1 in	410.0 mm	16.1 in	410.0 mm	16.1 in	410.0 mm	16.1 in
L REACH	370.6 mm	14.6 in	378.8 mm	14.9 in	384.0 mm	15.1 in	388.9 mm	15.3 in	394.5 mm	15.5 in	400.0 mm	15.7 in	403.4 mm	15.9 in
M STACK	502.6 mm	19.8 in	509.0 mm	20.0 in	526.7 mm	20.7 in	547.5 mm	21.6 in	568.3 mm	22.4 in	588.5 mm	23.2 in	607.7 mm	23.9 in
N STEM LENGTH	90.0 mm	3.5 in	90.0 mm	3.5 in	100.0 mm	3.9 in	110.0 mm	4.3 in	110.0 mm	4.3 in	120.0 mm	4.7 in	120.0 mm	4.7 in