



ADDICT RC

ADDICT RC: ULTIMATE, PREMIUM, PRO, 10, 15, 20, 30

	XXS/47		XS/49		S/52		M/54		L/56		XL/58		XXL/61	
A HEAD TUBE ANGLE	70.5°		71.0°		72.0°		72.5°		73.0°		73.3°		73.3°	
B HEAD TUBE LENGTH	97.0 mm	3.8 in	102.0 mm	4.0 in	115.0 mm	4.5 in	135.0 mm	5.3 in	155.0 mm	6.1 in	175.0 mm	6.9 in	193.0 mm	7.6 in
C TOP TUBE HORIZONTAL	520.0 mm	20.5 in	530.0 mm	20.9 in	540.0 mm	21.3 in	550.0 mm	21.7 in	565.0 mm	22.2 in	580.0 mm	22.8 in	600.0 mm	23.6 in
D STANDOVER HEIGHT	720.0 mm	28.3 in	740.0 mm	29.1 in	755.0 mm	29.7 in	778.0 mm	30.6 in	798.0 mm	31.4 in	818.0 mm	32.2 in	838.0 mm	33.0 in
E BB OFFSET	-70.0 mm	-2.8 in	-70.0 mm	-2.8 in	-70.0 mm	-2.8 in	-70.0 mm	-2.8 in	-70.0 mm	-2.8 in	-70.0 mm	-2.8 in	-70.0 mm	-2.8 in
F BB HEIGHT	274.5 mm	10.8 in	274.5 mm	10.8 in	274.5 mm	10.8 in	274.5 mm	10.8 in	274.5 mm	10.8 in	274.5 mm	10.8 in	274.5 mm	10.8 in
G WHEEL BASE	987.5 mm	38.9 in	994.0 mm	39.1 in	991.0 mm	39.0 in	992.0 mm	39.1 in	1'000.0 mm	39.4 in	1'008.0 mm	39.7 in	1'023.0 mm	40.3 in
H BB CENTER TO TOPTUBE CENTER	410.0 mm	16.1 in	430.0 mm	16.9 in	460.0 mm	18.1 in	480.0 mm	18.9 in	500.0 mm	19.7 in	520.0 mm	20.5 in	550.0 mm	21.7 in
I BB CENTER TO TOP OF SEATTUBE	470.0 mm	18.5 in	490.0 mm	19.3 in	520.0 mm	20.5 in	540.0 mm	21.3 in	560.0 mm	22.0 in	580.0 mm	22.8 in	610.0 mm	24.0 in
J SEAT ANGLE	74.5°		74.5°		74.0°		73.6°		73.3°		73.0°		72.5°	
K CHAINSTAY	410.0 mm	16.1 in	410.0 mm	16.1 in	410.0 mm	16.1 in	410.0 mm	16.1 in	410.0 mm	16.1 in	410.0 mm	16.1 in	410.0 mm	16.1 in
L REACH	454.0 mm	17.9 in	463.0 mm	18.2 in	474.0 mm	18.7 in	485.0 mm	19.1 in	492.0 mm	19.4 in	507.0 mm	20.0 in	518.0 mm	20.4 in
M STACK	563.0 mm	22.2 in	570.0 mm	22.4 in	586.0 mm	23.1 in	605.0 mm	23.8 in	627.5 mm	24.7 in	648.0 mm	25.5 in	667.0 mm	26.3 in
N STEM LENGTH	90.0 mm	3.5 in	90.0 mm	3.5 in	100.0 mm	3.9 in	110.0 mm	4.3 in	110.0 mm	4.3 in	120.0 mm	4.7 in	120.0 mm	4.7 in
O CENTRE SADDLE - CENTRE BAR (HOR.)	635.0 mm	25.0 in	650.0 mm	25.6 in	674.0 mm	26.5 in	694.0 mm	27.3 in	710.0 mm	28.0 in	736.0 mm	29.0 in	761.0 mm	30.0 in
P CENTRE SADDLE - CENTRE BAR (VERT.)	92.0 mm	3.6 in	105.0 mm	4.1 in	106.0 mm	4.2 in	103.0 mm	4.1 in	100.0 mm	3.9 in	106.0 mm	4.2 in	115.0 mm	4.5 in