



## ASPECT

**ASPECT:** 910, 920, 930, 940, 950, 960, 970, 980

	XS		S		M		L		XL		XXL	
A HEAD TUBE ANGLE	68.5°		68.5°		68.5°		68.5°		68.5°		68.5°	
B HEAD TUBE LENGTH	95.0 mm	3.7 in	100.0 mm	3.9 in	110.0 mm	4.3 in	120.0 mm	4.7 in	135.0 mm	5.3 in	150.0 mm	5.9 in
C TOP TUBE HORIZONTAL	560.0 mm	22.0 in	585.0 mm	23.0 in	600.0 mm	23.6 in	615.0 mm	24.2 in	635.0 mm	25.0 in	655.0 mm	25.8 in
D STANDOVER HEIGHT	743.0 mm	29.3 in	771.0 mm	30.4 in	783.0 mm	30.8 in	821.0 mm	32.3 in	857.0 mm	33.7 in	891.0 mm	35.1 in
E BB OFFSET	-60.0 mm	-2.4 in	-60.0 mm	-2.4 in	-60.0 mm	-2.4 in	-60.0 mm	-2.4 in	-60.0 mm	-2.4 in	-60.0 mm	-2.4 in
F BB HEIGHT	316.0 mm 12.4 in											
G WHEEL BASE	1102.0 mm	43.4 in	1090.0 mm	42.9 in	1102.0 mm	43.4 in	1123.0 mm	44.2 in	1144.0 mm	45.0 in	1164.0 mm	45.8 in
H BB CENTER TO TOPTUBE CENTER	309.0 mm	12.2 in	349.0 mm	13.7 in	394.0 mm	15.5 in	434.0 mm	17.1 in	484.0 mm	19.1 in	534.0 mm	21.0 in
I BB CENTER TO TOP OF SEATTUBE	355.0 mm	14.0 in	395.0 mm	15.6 in	440.0 mm	17.3 in	480.0 mm	18.9 in	530.0 mm	20.9 in	580.0 mm	22.8 in
J SEAT ANGLE	73.5°		73.5°		73.5°		73.5°		73.5°		73.5°	
K CHAINSTAY	450.0 mm	17.7 in	450.0 mm	17.7 in	450.0 mm	17.7 in	450.0 mm	17.7 in	450.0 mm	17.7 in	450.0 mm	17.7 in
L REACH	388.0 mm	15.3 in	406.0 mm	16.0 in	419.0 mm	16.5 in	431.0 mm	17.0 in	447.0 mm	17.6 in	463.0 mm	18.2 in
M STACK	580.0 mm	22.8 in	603.0 mm	23.7 in	612.0 mm	24.1 in	622.0 mm	24.5 in	636.0 mm	25.0 in	649.0 mm	25.6 in
N STEM LENGTH	50.0 mm	2.0 in	60.0 mm	2.4 in	70.0 mm	2.8 in	80.0 mm	3.1 in	90.0 mm	3.5 in	100.0 mm	3.9 in