



| | | MM | INCHES | | | | | | |
|----|------------------------------|----------|----------|----------|----------|----------|-----------|----------|------|
| | | | X57 | S7 | M7 | M9 | L9 | XL9 | XXL9 |
| A | BB CENTER TO TOP OF SEATTUBE | 360 MM | 405 MM | 445 MM | 445 MM | 485 MM | 525 MM | 565 MM | |
| B | TOP TUBE PARALLEL | 570 MM | 577 MM | 586 MM | 587 MM | 599 MM | 612 MM | 632 MM | |
| B* | TOP TUBE HORIZONTAL | 580 MM | 595 MM | 610 MM | 610 MM | 625 MM | 640 MM | 660 MM | |
| C | CHAINSTAY | 435 MM | 435 MM | 435 MM | 458 MM | 458 MM | 458 MM | 458 MM | |
| D | HEADTUBE LENGTH | 110 MM | 125 MM | 135 MM | 110 MM | 120 MM | 130 MM | 145 MM | |
| E | HEAD ANGLE | 69,0° | 69,0° | 69,0° | 69,0° | 69,0° | 69,0° | 69,0° | |
| F | SEAT ANGLE | 73,5° | 73,5° | 73,5° | 73,5° | 73,5° | 73,5° | 73,5° | |
| H | BB OFFSET | -56 MM | -56 MM | -56 MM | -70 MM | -70 MM | -70 MM | -70 MM | |
| K | WHEELBASE | 1.089 MM | 1.105 MM | 1.121 MM | 1.142 MM | 1.158 MM | 1.174 MM | 1.195 MM | |
| L | STANDOVER HEIGHT | 700 MM | 734 MM | 762 MM | 771 MM | 798 MM | 825 MM | 854 MM | |
| M | STACK | 597 MM | 611 MM | 621 MM | 629 MM | 638 MM | 647 MM | 661 MM | |
| N | REACH | 404 MM | 416 MM | 428 MM | 426 MM | 438 MM | 451 MM | 466 MM | |
| | FORK LENGTH | 483 MM | 483 MM | 483 MM | 503 MM | 503 MM | 503 MM | 503 MM | |
| | FORK RAKE | 42 MM | 42 MM | 42 MM | 46 MM | 46 MM | 46 MM | 46 MM | |
| G | SEATPOST DIAMETER | | | | | | 27,2 MM | | |
| I | SHOCK DIMENSION | | | | | | | | |
| | HEADSET DIMENSION | | | | | | Z544/Z544 | | |
| | BB STANDARD | | | | | | BSA68 | | |
| | HANGER TYPE | | | | | | 273561 | | |
| | MAX. ROTOR SIZE | | | | | | 180 MM | | |