



MM INCHES

	XXS/47	XS/49	S/52	M/54	L/56	XL/58	XXL/61
A HEAD TUBE ANGLE / ANGLE TUBE DE DIRECTION	70.5°	71.0°	72.0°	72.5°	73.0°	73.3°	73.3°
B HEAD TUBE LENGTH / HAUTEUR TUBE DE DIRECTION	95.0 MM	105.0 MM	125.0 MM	145.0 MM	165.0 MM	185.0 MM	205.0 MM
C TOP TUBE HORIZONTAL / LONGUEUR HORIZONTALE TUBE SUPÉRIEUR	515.0 MM	525.0 MM	540.0 MM	555.0 MM	570.0 MM	585.0 MM	600.0 MM
D STANDOVER HEIGHT / HAUTEUR ENTRE-JAMBES	732.0 MM	747.0 MM	775.0 MM	790.0 MM	812.0 MM	835.0 MM	848.0 MM
E BB OFFSET / DEPORT AXE DE PÉDALIER	-70.0 MM	-70.0 MM	-70.0 MM	-70.0 MM	-70.0 MM	-70.0 MM	-70.0 MM
F BB HEIGHT / HAUTEUR AXE DE PÉDALIER	275.3 MM	275.3 MM	275.3 MM	275.3 MM	275.3 MM	275.3 MM	275.3 MM
G WHEEL BASE / ENTRAXE ROUES	996.7 MM	1,003.0 MM	1,005.0 MM	1,010.6 MM	1,015.4 MM	1,022.8 MM	1,036.5 MM
H BB CENTER TO TOP TUBE CENTER / DIST. BOITIER - MILIEU TUBE SUPÉRIEUR	415.0 MM	435.0 MM	465.0 MM	485.0 MM	505.0 MM	525.0 MM	540.0 MM
I BB CENTER TO TOP OF SEATTUBE / DIST. BOITIER - SOMMET TUBE DE SELLE	455.0 MM	475.0 MM	505.0 MM	525.0 MM	545.0 MM	565.0 MM	580.0 MM
J SEAT ANGLE / ANGLE TUBE DE SELLE	75.0°	75.0°	74.5°	74.0°	73.5°	73.1°	73.0°
K CHAINSTAY / LONGUEUR DES BASES	420.0 MM	420.0 MM	420.0 MM	420.0 MM	420.0 MM	420.0 MM	420.0 MM
L REACH / REACH	376.3 MM	383.2 MM	387.0 MM	390.9 MM	394.3 MM	398.6 MM	406.6 MM
M STACK / STACK	517.8 MM	529.1 MM	551.6 MM	572.4 MM	593.3 MM	613.6 MM	632.7 MM
N STEM LENGTH / LONGUEUR POTENCE	73.0 MM	83.0 MM	93.0 MM	103.0 MM	103.0 MM	113.0 MM	113.0 MM